

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/014569 A1

(51) International Patent Classification?: **B05B 17/06**

OLN (GB). **POLLOCK**, Neil [GB/GB]; 20 Coombelands, Royston, Hertfordshire SG8 7DW (GB). **SANT**, Andrew, **Jonathan** [GB/GB]; 35 Stanbury Close, Fen Ditton, Cambridge, Cambridgeshire CB5 8UP (GB).

(21) International Application Number:
PCT/EP2003/008482

(22) International Filing Date: 31 July 2003 (31.07.2003)

(74) Agents: **HOFFMANN EITLE** et al.; Arabellastrasse 4, 81925 München (DE).

(25) Filing Language: English

(81) Designated States (*national*): JP, US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(30) Priority Data:
02016972.8 2 August 2002 (02.08.2002) EP

(71) Applicant (*for all designated States except US*): **PARI GMBH SPEZIALISTEN FÜR EFFEKTIVE INHALATION** [DE/DE]; Moosstrasse 9, 82319 Starnberg (DE).

Published:


- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **URICH**, Markus [DE/DE]; Arno-Assmann-Strasse 9, 81739 München (DE). **HYDE**, Samuel, Charles, William [GB/GB]; 66 Girton Road, Girton, Cambridge, Cambridgeshire CB3

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLUID DROPLET PRODUCTION APPARATUS AND METHOD



(57) Abstract: A fluid dispersion device comprises a substrate (3) having an outer section (25) and an inner section (26), said inner section (26) of the substrate (3) having an aperture (11), a dispersion element (10) positioned at said aperture (11) of said substrate (3), and an actuator (4) arranged to coaxially surround said aperture (11) of said substrate (3), wherein the outer edge of said inner section (26) of said substrate (3) is coupled to said outer section (25) of said substrate (3) by a plurality of resilient members (81, 82, 83).



WO 2004/014569 A1

FLUID DROPLET PRODUCTION APPARATUS AND METHOD

In a variety of industrial fields, for example those
5 involved in the manufacturing of devices for the
administration of medicinal compounds, it is desirable to
find means for nebulising a fluid or liquid in a
controlled manner.

10 One known solution to this problem involves the agitation
of a membrane by means of a piezoelectric oscillator,
wherein the fluid to be nebulised is placed at one side of
said membrane such that the fluid is nebulised in a
controlled manner to provide fine liquid droplet sprays,
15 mists or aerosols on the other side of the membrane.

Such a device, as for example known from EP 0 615 470 A,
commonly comprises an annular substrate, on one side of
which is disposed an annular piezoelectric device, and on
20 the other side of which is placed a circular dispersion
element, all three elements being disposed coaxially. The
circular dispersion element may comprise a plurality of
fine diameter holes, substantially parallel to the axis of
the device, through which fluid passes to form droplets.

25 A device of this kind is shown in Figure 1A, while Figure
1B shows a cross-section of the device of 1A along the
lines of AA and how on the energizing of the piezoelectric
element 4, a standing wave is set up through the device as
a whole, having maxima at the centre of the device, where
30 the dispersion element or mesh 10 is located, and side
lobes nearer the circumference of the substrate.

A problem arises with the described device where it is
necessary to fixedly attach it to a housing. The ways of
35 doing this known in the prior art either result in an
undesirable influence on the oscillation characteristics
of the device or are difficult to handle, especially in

the case of a medical treatment device employing such a device.

One known method of securing the nebuliser known in the prior art, as indicated in Figure 1B, involves the provision of bearings 20, 21, 22 and 23 positioned so as to support the substrate 3 at points at which the standing wave present under oscillating conditions is known to be a minimum. Clearly, this solution is limited by practical considerations, such that in practice a significant deterioration in the performance of the nebuliser is experienced.

An alternative method known in the prior art, as indicated in Figure 1C, involves the clamping of the substrate 3 at an circumferential edge, involving using fixed clamps 24. Once again, this results in a significant deterioration in the performance in the nebuliser. If the clamping is achieved by means of a ring of a soft resilient material the small gaps between the ring 24 and the substrate 3 are prone to collect fluids or other substances causing hygiene problems.

As mentioned above, these and other prior art methods of fixedly securing the nebuliser device are disclosed in EP 0 615 470 A.

A further problem arising in these known techniques is that there are provided numerous devices which are prone to retention of stray matter in an undesirable manner, particularly in medical applications where hygiene is of particular importance.

According to the present invention from a first aspect there is provided a fluid dispersion device comprising a fixed frame 25, a substrate 3 having a central aperture 11, a dispersion element 10 positioned over said central aperture 11 of said substrate 3, and an annular actuator 4

arranged coaxially with said central aperture 11 of said substrate 3, wherein the outer edge of said substrate 3 is coupled to said fixed frame 25 by a plurality of resilient members 81, 82, 83.

5

According to a development of this first aspect of the invention, said plurality of resilient members 81, 82, 83 are serpentine in form.

10 According to a further development of this first aspect of the invention, said plurality of resilient members 81, 82, 83 are aligned radially about the axis of said central aperture 11 of said substrate 3.

15 According to a further development of this first aspect of the invention, said plurality of resilient members 81, 82, 83 are aligned at an angle to a line radiating from the centre of said central aperture 11 of said substrate 3.

20 According to a further development of this first aspect of the invention, said substrate 3, said fixed frame 25 and said resilient members 81, 82, 83 are formed as a single solid.

25 According to a further development of this first aspect of the invention, said annular actuator 4 is a piezoelectric device.

30 According to a further development of this first aspect of the invention, at least one of said resilient members 81, 82, 83 is disposed so as to carry an electronic signal to said annular actuator 4.

35 The present invention will now be described in more detail by reference to the following figures.

Figure 1A shows a plan view of a nebulising device as known in the prior art.

Figure 1B shows a cross-section of the nebulising device as known in the prior art secured in a first manner and how a standing wave exists in the nebulising device in operation.

Figure 1C shows a cross-section of the nebulising device as known in the prior art secured in a second manner.

Figure 2A shows a plan view of a nebuliser according to a first embodiment of the present invention.

Figure 2B shows a cross-section of the nebuliser of Figure 2A.

Figure 3A shows a plan view of a nebuliser according to a second embodiment of the present invention.

Figure 3B shows a cross-section of the nebuliser of Figure 3A.

Figure 4A shows a plan view of a nebuliser according to a third embodiment of the present invention.

Figure 4B shows a cross-section of the nebuliser of Figure 4A.

Figure 5 shows an example of a meandering / serpentine resilient member according to the invention.

Figure 6 shows another example of a meandering / serpentine resilient member according to the invention.

Figure 7 shows another example of the fluid dispersion device according to the invention having a non-meandering resilient member.

Figure 8 shows another embodiment of the fluid dispersion device according to the invention having attachment sections.

Figure 9 shows another embodiment of the fluid dispersion device according to the invention having outer partial section supported in a supporting structure.

In the following, a fluid dispersion device according to the invention will be described in detail with reference to Figures 2 to 8, said device comprising a substrate 3 having an outer section 25 and an inner section 26, said inner section 26 of the substrate 3 having an aperture 11, a dispersion element 10 positioned at said aperture 11 of said substrate 3 to cover the aperture, and an actuator 4 arranged to surround said aperture 11 of said substrate 3, wherein the outer edge of said inner section 26 of said substrate 3 is coupled to said outer section 25 of said substrate 3 by a plurality of resilient members 81, 82, 83.

According to a first embodiment of the present invention, as shown in Figures 2A and 2B, there is provided a nebulising arrangement comprising a substrate 3, a piezoelectric element 4, and a nebulising element 1. The piezoelectric element 4 is annular in shape, while the substrate 3 comprises openings so as to form an inner annular section 26 and an outer annular section 25, these two annular sections being connected, preferably in the same plane, by a plurality of connecting spoke elements 81, 82 and 83. The piezoelectric element 4 is attached to one side of the inner annular section 26 of the substrate 3, and is arranged coaxially therewith. Similarly, the nebulising element 1 is disposed on the opposite side of inner annular section 26 of the substrate 3, and coaxially with said substrate 3 and piezoelectric element 4, so as

to cover the opening in the center of the inner annular section 26 of the substrate 3. The nebulising element 1 may also be provided on the same side of the substrate 3 as the piezoelectric element 4 or may be formed as one piece with said substrate 3 by thinning the substrate 3 at the area defined by said aperture and by providing fluid passage ways through the thinned portion of the substrate.

The dispersion element 1 is preferably dome shaped, as shown in Figure 2B, or may be substantially flat. Further, if the liquid is provided on one side of the dispersion element and the fine droplet spray is to be generated on the other side, the dispersion element 1 is provided with fine holes or openings 10 to allow the liquid to pass.

The outer annular section 25 of the nebulising device according to the invention may be fixed or clamped to a housing (not shown) as known in the prior art, so as to be held substantially immobile with respect to the housing. By means of the connecting spoke elements 81, 82, 83 the inner annular section 26 is supported and thereby securely attached to the outer annular section 25.

In operation, an electrical signal is applied to the piezoelectric element 4 in an appropriate manner, for example through the inner section 26 of the substrate 3 and a further electrode disposed on the opposite side of the piezoelectric element 4. The electrical signal may be carried by at least one of the resilient members 81, 82, 83 to the inner section 26 and by the outer section 25 to the at least one resilient spoke element 81, 82, 83, respectively. By applying an appropriate electrical signal to the piezoelectric element 4, contractions and expansions of the piezoelectric element 4 are induced in a direction parallel to the plane of the substrate 3 causing an oscillation of the structure comprising the nebulising element 1, the inner annular section 26, and the piezoelectric element 4 as whole in a direction

substantially perpendicular to said plane. By controlling the signal, not only the behavior of the piezoelectric element 4 but also the oscillation of the overall device is controlled, and thereby the generation of the fine droplet spray as well.

Since the inner annular section 26 is supported only via the connecting spoke elements 81, 82, 83, the deterioration in the performance of the nebulising device caused by its mounting structure, is substantially less than that experienced in the prior art, due to the resilience of the connecting spoke elements 81, 82, 83. The resilience characteristics of the connecting spoke elements 81, 82, 83 can easily be adapted by defining the shape, i.e. in the first embodiment the length, width and thickness of each resilient member 81, 82, 83. The resilience can further be influenced according to design requirements by selecting an appropriate material, for example, stainless steel etc.

The connecting spoke elements 81, 82, 83 according to the invention reduce the deteriorating influence of the support structure on the nebulising device due to the adaption of the resilience characteristics whereby the forces applied to those ends of the connecting spoke element which are attached to the inner annular section 26 are reflected from the other ends of the connecting spoke elements, i.e. which are attached to the outer annular section 26. The forces applied to the connecting spoke elements 81, 82, 83 due to the oscillation of the inner annular section 26 causes the adapted connecting spoke elements to oscillate in or near resonance such that a wave induced by the forces applied exhibits an oscillation node at the other end, i.e. the end attached to the outer annular section 25.

As mentioned above, the membrane or mesh 1, i.e. the dispersion element, may be formed with a central dome as shown in Figures 2 to 4, or may be a flat disk, and may be

formed of stainless steel, silver coated nickel or other suitable material. The dome may be formed by stamping or deep drawing a flat disk to form the desired shape.

- 5 The inner and the outer section 25, 26 of the substrate 3 and the resilient members 81, 82, 83 may be, for example, of stainless steel and may be formed as a solid or as individual components, also of different materials.
- 10 The membrane may, for example, be welded to the substrate, by means of a laser.

A second embodiment of the present invention is shown in figures 3A and 3B. The nebulising device according to this
15 embodiment is provided with all elements of the first embodiment, which are numbered correspondingly. The second embodiment differs from the first embodiment in that the connecting spoke elements 81, 82, 83 are formed as serpentine or meandering elements. By this means, the
20 degree of influence of the mounting on the oscillations of the central arrangement, comprising at least the dispersion element 1, the inner section 26 of the substrate 3 and the actuator 4, is further reduced without an increase in the distance between the outer edge of the
25 inner annular section of the substrate 3 and the inner edge of the outer annular section 25. Still the inner annular section 26 is safely supported similar to the first embodiment.

30 A third embodiment of the present invention is shown in figures 4A and 4B. The nebulising device according to this embodiment is provided with all elements of the second embodiment, which are numbered correspondingly. The third embodiment differs from the second in that the connecting
35 spoke elements 81, 82, 83 are formed as serpentine elements. In general, serpentine shaped elements can be defined with reference to a longitudinal axis LA as shown in Figure 5. The example of Figure 5 resembles the

waveform of a sinusoidal wave and is asymmetrical as two maxima of the sinus wave are provided on one side of longitudinal axis LA and only a single maximum is provided on the other side. However, still within the scope of the present invention, a symmetrical arrangement of maxima on both sides of longitudinal axis LA may be provided. Also, any other serpentine or meandering shape may be employed for embodying the serpentine resilient elements according to the third embodiment of the invention.

As a further example, Figure 6 shows a serpentine resilient element being assembled by two triangular shaped sections of which one is provided on either side of longitudinal axis, respectively. Obviously, more than two triangular shaped sections may be provided. Also, rectangular shaped sections, semi circular shaped sections, saw-tooth shaped section, and any section of any other shape may be used. The individual section may be of different shape as well, so that, for example, a triangular shaped section may be followed by a rectangular shaped section. Again, as should be obvious, more than two sections may be combined to form a resilient element.

In Figures 5 and 6, the longitudinal axis LA is shown as a straight line. However, in general and also with respect to the third embodiment above, the longitudinal axis may be understood to be part of circle as shown as a dotted line in Figure 4A. However, in view of the typical relationship between the radius of said circle and the length of the individual meandering resilient element, the longitudinal axis LA can be considered as a straight axis. This assumption has been used in the above description of the general shape of the meandering serpentine resilient elements according to the third embodiment of the invention with respect to Figures 5 and 6.

According to the invention and as shown in Figure 4A, the meandering resilient elements 81, 82, 83 are disposed at an angle to a line radiating from the centre of said

central aperture 11 of the substrate 3. If the angle is substantially equal to 90° , as shown in Figure 4A, the ring shaped gap between the inner annular section 26 and the outer annular section 25 of the substrate 3 is minimized. The longitudinal axis of each serpentine shaped connecting spoke element 81, 82, 83 is arranged substantially tangential to the circle 9 shown as a dotted line in Figure 4A.

In other words, the serpentine elements are preferably disposed along a circular line 9 situated between the outer edge of the central portion 26 of the substrate 3 and the inner edge of the outer ring 25 and substantially concentric therewith. The two ends of each resilient element deviate from this line so as to join the outer edge of the inner portion 26 of the substrate 3 and the inner edge of the outer portion 25, respectively. By this means, the degree to which oscillations of the central portion 26 of the substrate 3 to which the piezoelectric element 4 is attached are negatively influenced by the mounting is reduced, with a minimum increase in the distance between the outer edge of the central portion 26 of the substrate 3, and the inner edge of the outer ring 25.

A fourth embodiment of the present invention is shown in figure 7. The nebulising device according to this embodiment is provided with many elements of the third embodiment, which are numbered correspondingly. The fourth embodiment differs from the third embodiment in that the connecting resilient elements 81, 82, 83 are formed as non-meandering resilient members. According to the invention and as shown in Figure 7, the non-meandering resilient members 81, 82, 83 are disposed at an angle to a line radiating from the center of said central aperture 11 of the substrate 3. If the angle is substantially equal to 90° , as shown in Figure 7, the ring shaped gap between the inner annular section 26 and the outer annular section 25

of the substrate 3 is minimized. It should be noted that the gap is in general smaller when non-meandering resilient members are used. Further, the non-meandering resilient elements may be arc-shaped to extend
5 substantially in parallel to the edges towards the gap of the inner and the outer annular section 26 and 25, respectively. It is preferable to arrange the longitudinal axis of each non-meandering connecting spoke element 81, 82, 83 substantially tangential to the circle 9 shown as a
10 dotted line in Figure 7.

In other words, the non-meandering elements are preferably disposed along a circular line 9 situated between the outer edge of the central portion 26 of the substrate 3
15 and the inner edge of the outer ring 25 and in a preferred embodiment substantially concentric therewith. The two ends of each resilient element deviate from this line so as to join the outer edge of the inner portion 26 of the substrate 3 and the inner edge of the outer portion 25,
20 respectively. Thereby, the degree to which oscillations of the central portion 26 of the substrate 3 to which the piezoelectric element 4 is attached are negatively influenced by the mounting is reduced, with a minimum increase in the distance between the outer edge of the
25 central portion 26 of the substrate 3, and the inner edge of the outer ring 25.

In order to facilitate manufacturing of the device according to the invention and also to further reduce the
30 deteriorating effect caused by the mounting structure, the outer section 25 and the inner section 26 may be manufactured separately and the connecting spoke elements 81, of which only one is shown in Figure 8 as an example, may be attached to corresponding attachment sections 25A
35 provided integral with the outer section 25 of the substrate 3, as shown in Figure 8. The connecting resilient spoke members 81 and the inner section 26 of the substrate 3 are advantageously manufactured as one piece.

The attaching of the resilient elements 81 may be achieved by welding or otherwise at point 25B any time during the manufacturing process. Thereby, the manufacturing of the outer section 25 and its further supporting structure may be performed separately from the manufacturing of the inner section 26 and the resilient spoke elements 81.

Further, the inner section 26 may be provided with attachment sections 26A similar to the outer section 25. The resilient spoke elements 81 may be welded at welding point 26B or otherwise attached to the inner section 26. Thus, the resilient elements 81 may be manufactured separately from the inner and outer section of the substrate 3 so that the resilient elements 81 may be of a material different from the substrate 3.

Of course, the resilient members 81 may be formed in one piece with the outer section 25 of the substrate 3 and may be attached at attachment point 26B of an attachment section 26A of the inner section 26 of the substrate 3 in an appropriate step of the manufacturing process as described above.

As shown in Figure 9, if the outer section 25 of the substrate 3 is molded into a supporting body 30 of, for example a plastic material, or if another support structure 30 is provided, the outer section 25 may be provided in the form of outer partial sections 25'. In such a configuration the outer partial sections 25' are preferably first molded into or otherwise fixed to a supporting structure 30 which is, for example ring-shaped, to safely hold the partial sections 25' similar to the positions otherwise provided for each partial section 25' by being an integral part the outer annular section 25. It is preferred to manufacture the outer partial sections 25' separately and to fix the partial sections 25' to the supporting structure 30 in a separate manufacturing step. Thereafter, the inner section 26 and the resilient members

81, 82, 83, are respectively attached to the partial outer sections 25' by, for example welding the resilient elements 81, 82, 83 to the attachment parts 25A of the outer partial sections 25' protruding from said supporting
5 body 30.

Claims

1. A fluid dispersion device comprising

- a substrate (3) having an outer section (25) and an inner section (26), said inner section (26) of the substrate (3) having an aperture (11),
- a dispersion element (10) positioned at said aperture (11) of said substrate (3), and
- an actuator (4) arranged to coaxially surround said aperture (11) of said substrate (3),

wherein the outer edge of said inner section (26) of said substrate (3) is coupled to said outer section (25) of said substrate by a plurality of resilient members (81, 82, 83).

2. The fluid dispersion device of claim 1, wherein said aperture is arranged centrally to said inner section (26) and is circularly shaped and wherein said actuator (4) is annularly shaped.

3. The fluid dispersion device of claim 1 or 2, wherein said plurality of resilient members (81, 82, 83) are serpentine / meandering in form.

4. The fluid dispersion device of claim 2 or 3, wherein said plurality of resilient members (81, 82, 83) are aligned radially about the axis of said central aperture (11) of said substrate (3).

5. The fluid dispersion device of claim 2 or 3, wherein said plurality of resilient members (81, 82, 83) are aligned at an angle to a line radiating from the centre of said central aperture (11) of said substrate (3).

6. The fluid dispersion device of any preceding claim wherein said inner section (26), said outer section (25) and said resilient members (81, 82, 83) are formed as a single solid.

7. The fluid dispersion device of any one of claims 1 to 4, wherein said inner section (26) and said resilient members (81, 82, 83) are formed as a single solid, wherein said outer section (25) is provided with attachment sections (25A) and wherein said resilient members (81, 82, 83) are attached to said attachment sections (25A).

8. The fluid dispersion device of any one of claims 1 to 4, wherein said outer section (25) and said resilient members (81, 82, 83) are formed as a single solid, wherein said inner section (26) is provided with attachment sections (26A) and wherein said resilient members (81, 82, 83) are attached to said attachment sections (25A).

9. The fluid dispersion device of any one of claims 1 to 4, wherein said outer section (25) is provided with attachment sections (25A) and said inner section (26) is provided with attachment sections (26A) and wherein said resilient members (81, 82, 83) are attached to said attachment sections (25A, 26A).

10. The fluid dispersion device of any one of the preceding claims, wherein the outer section (25) is provided by a plurality of outer partial sections (25') which are positioned by means of a supporting structure (30) which is preferably ring-shaped.

11. The fluid dispersion device of any preceding claim, wherein said annular actuator (4) is a piezoelectric device.

12. The fluid dispersion device of any preceding claim, wherein at least one of said resilient members (81, 82, 83) is adapted to carry an electrical signal provided for said actuator (4).

13. The fluid dispersion device of claim 11, wherein the inner section (26) of the substrate (3) is adapted to

carry an electrical signal provided for said actuator (4) via the at least one resilient member (81, 82, 83).

14. The fluid dispersion device of claim 11 or 12, wherein
5 the outer section (26) of the substrate (3) is adapted to carry an electrical signal provided for said actuator (4) to the at least one resilient member (81, 82, 83).

15. The fluid dispersion device of any one of the
10 preceding claims, wherein the dispersion element (10) is provided as an integral part of said substrate (3).

Fig. 1a Prior Art




Fig. 1b Prior Art




Fig. 1c Prior Art




Fig. 2a




Fig. 2b




Fig. 3a




Fig. 3b




Fig. 4a




Fig. 4b




Fig. 5




Fig. 6




Fig. 7




Fig. 8





Fig. 9



INTERNATIONAL SEARCH REPORT

inter Application No

PCT/JP03/08482

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B05B17/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B05B A61M F16F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 263 076 A (BESPAK PLC) 14 July 1993 (1993-07-14) page 11, line 14 -page 12, line 17; figures 7-9	1, 2, 4, 6, 11, 15
A	----- PATENT ABSTRACTS OF JAPAN vol. 008, no. 118 (C-226), 31 May 1984 (1984-05-31) & JP 59 032971 A (MATSUSHITA DENKI SANGYO KK), 22 February 1984 (1984-02-22) abstract	1, 2, 11, 15
A	----- PATENT ABSTRACTS OF JAPAN vol. 010, no. 023 (C-325), 29 January 1986 (1986-01-29) & JP 60 175566 A (MATSUSHITA DENKI SANGYO KK), 9 September 1985 (1985-09-09) abstract	1, 2, 11, 15
	----- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *S* document member of the same patent family

Date of the actual completion of the international search

25 November 2003

Date of mailing of the international search report

17/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Daintith, E

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP03/08482

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 348 058 A (RADIOTECHNIQUE COMPELEC) 10 November 1977. (1977-11-10) figures	1
A	EP 1 214 986 A (SIEMENS AG) 19 June 2002 (2002-06-19) figures	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 03/08482

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2263076	A	14-07-1993	AT 93418 T	15-09-1993
			AT 143295 T	15-10-1996
			AT 194511 T	15-07-2000
			AU 637658 B2	03-06-1993
			AU 6789790 A	23-07-1992
			BR 9006291 A	24-09-1991
			CA 2031907 A1	13-06-1991
			CN 1054916 A , B	02-10-1991
			DE 69002926 D1	30-09-1993
			DE 69028718 D1	31-10-1996
			DE 69033591 D1	17-08-2000
			DE 69033591 T2	23-11-2000
			DK 432992 T3	10-01-1994
			DK 542723 T3	03-03-1997
			EP 0432992 A1	19-06-1991
			EP 0542723 A2	19-05-1993
			EP 0718046 A2	26-06-1996
			ES 2030348 A6	16-10-1992
			ES 2043293 T3	16-12-1993
			ES 2092146 T3	16-11-1996
			FI 906089 A	13-06-1991
			FI 931780 A	20-04-1993
			FR 2655572 A1	14-06-1991
			GB 2240494 A , B	07-08-1991
			IE 904468 A1	19-06-1991
			IL 96597 A	12-04-1994
			IN 179463 A1	11-10-1997
			IT 1244181 B	08-07-1994
			JP 1917114 C	23-03-1995
			JP 4100557 A	02-04-1992
			JP 6040984 B	01-06-1994
			KR 152086 B1	01-10-1998
			MX 172730 B	10-01-1994
			NO 905350 A , B ,	13-06-1991
			NZ 236418 A	23-12-1992
			PT 96169 A , B	31-08-1992
			RU 2051755 C1	10-01-1996
			US 5152456 A	06-10-1992
			US 5261601 A	16-11-1993
			ZA 9009776 A	26-08-1992
JP 59032971	A	22-02-1984	NONE	
JP 60175566	A	09-09-1985	JP 1666435 C	29-05-1992
			JP 3029469 B	24-04-1991
FR 2348058	A	10-11-1977	FR 2348058 A1	10-11-1977
			BE 853572 A1	14-10-1977
EP 1214986	A	19-06-2002	EP 1214986 A1	19-06-2002
			WO 0247828 A1	20-06-2002
			EP 1341615 A1	10-09-2003